



MAUSER
S P E Z I A L

卓越的接缝 Excellence in seaming

MI5530-E0/5530-E3

电脑一体式(直驱平台式/电动剪线)绷缝机
Computer Integrated (Direct Drive Platform/Electric Thread Trimmer) Interlock Sewing Machine



“毛瑟”品牌的历史里程碑 / *Milestones in the history of trademark “MAUSER”*

- 1812 The royal armaments factory in Oberndorf is founded
位于奥伯恩多夫的皇家军备制造厂成立
- 1872 Company founded by the Mauser brothers
毛瑟兄弟成立公司
- 1920 After world war one, the company expands its portfolio, inter alia to measuring devices and automobiles, like the Mauser Mono-Track-Car
第一次世界大战后，公司主要投资于测量仪器和汽车行业，比如毛瑟的单轨道汽车
- 1923 The first Mauser special sewing machine is introduced. (German Patent: DE 410 952)
German T : 336 284 is established
第一台毛瑟特种缝纫机诞生。(德国专利号: DE 410 952)
德国商标336 284成立
- 1929 At the international exhibition in Barcelona, Mauser is awarded with the Grand Prix for its sewing machine Type BHE
在巴塞罗那的国际展览会上，毛瑟凭借缝纫机机种“BHE”被授予大奖
- 1950 The production of industrial sewing machines becomes part of IVK Augsburg AG “Mauser” introduces automatically lubricated coverlock sewing machines and the “Mauserlock-Armabwärts-Viernadel-Sechsfadenmaschine” (“Mauserlock” four needles six thread feed-off-the-arm machine)
工业缝纫机成为卡尔斯鲁厄奥格斯堡工业厂股份公司生产产品的一部分
毛瑟引进有自动供油功能的包缝和绷缝两用机和“Mauserlock” (四针六线曲臂机)
- The trade mark “MAUSER SPEZIAL” is established (German TMs DE 618 326)
“MAUSER SPEZIAL” 商标成立。
(德国商标号: DE 618 326)
- 1975 The “MAUSER SPEZIAL”-product line is bought by G. M. Pfaff AG (today Pfaff Industriesysteme und Maschinen GmbH)
G. M. Pfaff AG 收购“MAUSER SPEZIAL”的产品线(现百福工业系统及机械有限责任公司)
- 2010 New Logo and TMs are introduced
European TMs: 9 928 805, 9 359 167
新的徽标和商标成立。
欧洲商标号: 9 928 805, 9 359 167
- 2013 SG Group Co. Ltd. takes over Pfaff
上工申贝(集团)股份有限公司收购百福公司
- 2016 New Logo and TMs are introduced
新的徽标和商标成立。





机器说明/Machine Description

本系列机型分平台式绷缝机。平台是适合于长片布料的缝纫，该系列机型可分别选配多种附加装置、功能和扩展系列。
如：盖缝，滚条缝，花边松紧带，下摆折边，自动剪线，自动抬压脚等功能。

This series of models is divided into two styles: platform type and barrel type. The platform type is suitable for sewing long pieces of fabric, and the tube type is suitable for sewing fabrics with cylindrical cuffs. This series of models can be equipped with various additional devices, functions and extended series.
Such as: cover seam, roll seam, lace elastic band, hem folding, automatic thread trimming, automatic presser foot lifting and other functions.

型号描述/Model Descriptions

553:平台式绷缝机
553:Flatbed Interlock Sewing Machine

01:基本款
01:Basic

02: 上滚条缝
02:Upper Rolling Strip Sewing

03: 盖缝
03:Cover Sewing

B:中厚类
Middle heavy

563:筒式绷缝机
563:Cylinder Interlock Sewing Machine

05: 花边松紧带
05:Lace Elastic Band

08: 下摆折边
08:Hem Hem

21B: 厚料地毯 (大针距)
21B:Thick Material Carpet (Large Needle Pitch)

C:厚类
Heavy

MI 5530 E0 - 01 B56 / 31

E0:一体直驱款
E0:Integrated Direct Drive

E3: 一体电动剪线款
E3:Integrated Electric Trimmer

56:针距5.6mm
56:Needle Pitch 5.6mm

64:针距6.4mm
64:Needle Pitch 6.4mm

31: 多功能 (02专用)
31:TMulti-function (02 dedicated)

技术参数/Technical Data



Model	Icon	Needle	Presser	Needle	Needle	Needle	mm	rpm	rpm	rpm	rpm	W	mm x mm x mm	kg
MI 5530-E0-01B56	—	3	5	5.6	0.5-1.3	4.4	31	5.5	5000	2	UY128GAS 11#	550	670X470X650	41.5/54
MI 5530-E0-02B56	—	3	5	5.6	0.5-1.3	4.4	31	5.5	5000	2	UY128GAS 11#	550	670X470X650	41.5/54
MI 5530-E0-02B56/31	—	3	5	5.6	0.5-1.3	4.4	31	5.5	5000	2	UY128GAS 11#	550	670X470X650	41.5/54
MI 5530-E0-03B56	—	3	5	5.6	0.5-1.3	4.4	31	5.5	5000	2	UY128GAS 11#	550	670X470X650	41.5/54
MI 5530-E3-01B56	★	3	5	5.6	0.5-1.3	4.4	31	5.5	5000	2	UY128GAS 11#	550	670X470X650	49/57.5
MI 5530-E3-02B56	★	3	5	5.6	0.5-1.3	4.4	31	5.5	5000	2	UY128GAS 11#	550	670X470X650	49/57.5

注: MI 5530-E0 标配为上工电控, MI 5530-E3 标配为鲍麦克斯电控。

Note: The standard configuration of MI5530-E0 is Shangong electric control, and the standard configuration of MI5530-E3 is Promax electric control.

本机优势/Advantages



自动剪线
Automatic thread trimming



一体电控、USB充电、LED灯、高效便捷
Integrated electronic control, USB charging, LED lights, efficient and convenient



剪线电磁铁
Electric trimmer device



线迹整齐美观
Neat and beautiful stitches



MAUSER
S P E Z I A L

技术参数:

最高缝纫速度:

5000RPM

Sewing Speed:

5000RPM

针数 / 线数:

3 针 / 5 线

Number of needles/threads::

3-pin/5-thread

压脚提升高度:

5.5mm

Lifting Height Of Presser Foot:

5.5mm

针杆行程:

31mm

Needle Bar Stroke:

31mm

马达:

直伺服电机 550W

Motor:

Direct drive servo motor 550W



一体电动剪线款 / Integrated Electric Thread Trimmer



关注企业微信公众号
上工申贝集团



关注企业微信公众号
DAPShanghai



上工申贝（集团）股份有限公司
Shang Gong Group Co., Ltd.

上海市浦东新区新金桥路1566号金苑楼
Jinyuan Building, 1566 Xinqinqiao Road,
Shanghai 201206, China

Tel :+(86)21 6393 8822

Fax:+(86)21 6307 8413

E-mail:info@dap-china.com

Internet:www.sgsbgroup.com